

TECHNICAL SPECIFICATIONS

DIMENSIONS AND WEIGHT

Width	700mm
Height	275 mm
Depth	260 mm
Weight	12 kg

EXTENSIONS AND INTERFACES

Accessories	Height Adj. Floor Fixing Plate Power Cable
Interfaces	Led Status Indicator Manual Charge Port On/Off Switch Lift Handle

POWER AND PERFORMANCE

Charge Time	2 hrs for %0 to %80 - 3 hrs for %0 to %100
Output	Li - Ion Profile / 29.5V - 40A
Input	100 - 240V AC, 50-60 Hz Max. 1500W

ENVIRONMENT

Operation Environment	Indoor
Operating Temperature Range	-30°C to 70°C
Storage Temperature Range	-40°C to 85°C
Humidity	20-90% non-condensing

SAFETY AND COMPLIANCES

Standards	EN-60335-2-29, CE IP 54
Charger Safety	Automatic Voltage Detection and Smart Charge Start, Short Circuit Protection, Reverse Polarity Protection Over Voltage Protection

CONTACT US



Serhat Mah. 1147. Cadde
No:11 06374
Ankara / TURKEY

ODTU Teknokent MET
B Blok No: 280/15 06520
Ankara / TURKEY

P : +90 312 227 0 235
<http://milvusrobotics.com>