

TECHNICAL SPECIFICATIONS

DIMENSIONS AND WEIGHT

Width	700mm
Height	275 mm
Depth	260 mm
Weight	9 kg

ENVIRONMENT

Operation Environment	Indoor
Operating Temperature Range	-30°C to 70°C
Storage Temperature Range	-40°C to 85°C
Humidity	20-90% non-condensing

EXTENSIONS AND INTERFACES

Accessories	Height Adj. Floor Fixing Plate Power Cable
Interfaces	Led Status Indicator Manual Charge Port On/Off Switch Lift Handle

SAFETY AND COMPLIANCES

Standards	EN-60335-2-29, CE IP 54
Charger Safety	Automatic Voltage Detection and Smart Charge Start, Short Circuit Protection, Reverse Polarity Protection Over Voltage Protection

POWER AND PERFORMANCE

Charge Time	2 hrs for %0 to %80 - 3 hrs for %0 to %100
Output	Li - Ion Profile/ 29.5V - 20A
Input	100 - 240V AC, 50-60 Hz Max. 1500W

CONTACT US



Serhat Mah. 1147. Cadde
No:11 06374
Ankara / TURKEY

ODTU Teknokent MET
B Blok No: 280/15 06520
Ankara / TURKEY

P : +90 312 227 0 235
<http://milvusrobotics.com>